

# PRODUCT DATASHEET

## LED Spot Cylinder Duo 1xGU10 Brushed Nickel

LED Spot Cylinder Duo | Surface mounted luminaires with adjustable GU10 spotlights



---

### Areas of application

- Indoor applications

---

### Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

---

### Product features

- Luminaire family features five versions with up to 6 spot heads
- Housing surface made of brushed and chrome nickel
- Adjustable head
- On/off switch on 1-head version for easy operation




TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 70.00 mm  |
| Width          | 109.00 mm |
| Height         | 120.00 mm |
| Product weight | 227.00 g  |



LED SPOT CYLINDER DUO  
1XGU10

Materials & Colors

|                                            |                       |
|--------------------------------------------|-----------------------|
| Product color                              | Brushed nickel chrome |
| Housing color                              | Brushed nickel chrome |
| Body material                              | Steel                 |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C                |

Application & Mounting

|                              |                             |
|------------------------------|-----------------------------|
| Ambient temperature range    | -20...+40 °C                |
| Temperature range at storage | -20...+80 °C                |
| Type of connection           | Terminal, 3-Pole (L, N, PE) |
| Type of protection           | IP20                        |
| Dimmable                     | No                          |
| Mounting type                | Surface                     |

|                          |      |
|--------------------------|------|
| Mounting location        | Wall |
| Adjustable               | Yes  |
| With light source        | No   |
| Replaceable light source | Yes  |
| Holder designation       | GU10 |

### Emergency lighting

|                                  |      |
|----------------------------------|------|
| Type of emergency operation test | None |
|----------------------------------|------|

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Product remark        | Maximum bulb wattage: 5 W LED / Available from January 2026 |
| Number of illuminants | 1                                                           |

### Safety advice

- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                   |
|------------------------------------------------------------------------------------|----------------------------------------|---------------------------------|
|  | User instruction / safety instructions | LED SPOT CYLINDER DUO G11239547 |
|  | Declarations of conformity             | LED Spotlights                  |
|  | Declarations of conformity UKCA        | LED Spotlights                  |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075852662 | Folding box<br>1             | 87 mm x 137 mm x 92 mm               | 275.00 g     | 1.10 dm <sup>3</sup> |
| 4058075852679 | Shipping box<br>4            | 180 mm x 145 mm x 190 mm             | 1290.00 g    | 4.96 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.