

# PRODUCT DATASHEET

## DALI ACU BT

## DALI ACU BT | Control units for light management systems



## Areas of application

- Offices
- Conference rooms
- Training rooms
- Classrooms
- Corridors
- Shop lighting

## Product benefits

- Control the light via Smartphone
- Adjustment of all settings via smartphone
- Plug and Play: Basic features usable without App
- Simplified startup thanks to predefined operation modes
- Intuitive manual dimming, switching and changing of colour temperature
- Up to 4 groups separately controllable
- Adjustable Offset for different groups
- Easy Scene creation via App
- Scene-recall via OSRAM DALI PRO PB coupler possible
- Firmware update over-the-air via Bluetooth possible
- Integrated DALI supply
- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)\*
- Selected DALI parameters changeable via APP

## Product features

- Compact light control with DALI interface
- Smart phone connection via Bluetooth to control and configure
- One DALI output channel (Broadcast or Groupcast)
- Up to 32 DALI luminaires connectable
- Supports up to 4 OSRAM DALI sensors and pushbutton couplers


- Daylight-dependent regulation and presence-dependent control of light
- Separate pushbutton input to operate via standard pushbutton
- Supports DALI DT8 Tunable White driver
- Outputs with electronical reversible overtemperature, short-circuit, overload protection
- Length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50 m
- Suitable for flush box mounting

## TECHNICAL DATA

### Electrical data

Nominal wattage	3.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Operating frequency	50/60 Hz

### Dimensions & Weight



Length	49 mm
Width	48.00 mm
Height	22.00 mm
Product weight	40.00 g

### Colors & materials

Product color	Light grey
---------------	------------

### Temperatures & operating conditions

Ambient temperature range	-20...+60 °C
---------------------------	--------------

### Additional product data

Number of control outputs	1
Number of connectable sensors	4
Max. connectable push button couplers / sensors	4
Commissioning App	App (Android/ iOS)
Groups	4

### Capabilities

Dimmable	No
Dimming interface	DALI
Type of installation	Luminaire integration/Integrated in flush device box

Transmitter range	15 m
-------------------	------







## Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

## EQUIPMENT / ACCESSORIES

– Free App for iOS and Android available at the app store

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DALI ACU BT Control
	Extended installation guide	DALI ACU BT Control
	Declarations of conformity	DALI ACU BT
	Declarations of conformity UKCA	DALI ACU BT UK
	Certificates	VDE
	EU Data Act	Connected Products and Related Software and Services

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899544819	Folding box 1	81 mm x 81 mm x 46 mm	57.00 g	0.30 dm <sup>3</sup>
4052899544826	Shipping box 60	344 mm x 254 mm x 278 mm	3847.00 g	24.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.